



A NERE - BLACK
nylon - delrin®

	D1 mm IN.	D2 mm IN.	D3 mm IN.	S mm IN.	G mm IN.
21.00	17 11/16	6,2 1/4	5 3/16	7 9/32	15 19/32
21.01	22 7/8	8,2 11/32	8 5/16	13,2 17/32	15,5 39/64
21.02	25 1	8,2 11/32	5 3/16	6,4 1/4	22 7/8
21.03	25 1	8,2 11/32	8 5/16	10 3/8	17,5 11/16
21.04	27 11/16	8,2 11/32	10 3/8	15 19/32	18 45/64
21.06	33,5 15/16	8,2 11/32	10 3/8	13 1/2	26 11/32
21.07	38 11/2	8,2 11/32	8 5/16	10 3/8	33 119/64
21.08	45 13/4	8,2 11/32	10 3/8	13,4 17/32	37 129/64
21.09	53 21/16	8,2 11/32	10 3/8	15,7 5/8	43 111/16
21.10	54 23/16	8,2 11/32	12 7/16	17,5 11/16	42 121/32

C lega leggera anodizzata dura a spessore + PTFE con inserto plastico
Hardcote + PTFE anodised aluminium with plastic insert

	D1 mm IN.	D2 mm IN.	D3 mm IN.	S mm IN.	G mm IN.
21.30	25 1	8,2 11/32	2,5 3/32	6,8 17/64	21 53/64
21.31	25 1	8,2 11/32	4 5/32	9,8 3/8	19,5 49/64
21.32	34 15/16	8,2 11/32	4 5/32	10,8 7/16	28,5 11/8
21.33	40 19/16	8,2 11/32	5 3/16	10,2 13/32	34 15/16
21.34	45 13/4	8,2 11/32	5 3/16	13,6 17/32	37 129/64
21.35	55 23/16	8,2 11/32	6 1/4	18 23/32	43 111/16
21.36	28 11/16	8,2 11/32	4 5/32	10,2 13/32	23 29/32
21.37	34 15/16	8,2 11/32	5 3/16	13,6 17/32	28 11/16

E inox con inserto plastico
inox with plastic insert

	D1 mm IN.	D2 mm IN.	D3 mm IN.	S mm IN.	G mm IN.
21.60	16 5/8	5,2 13/64	5 3/16	6,4 1/4	12,7 1/2

A BIANCHE - WHITE
delrin®

	D1 mm IN.	D2 mm IN.	D3 mm IN.	S mm IN.	G mm IN.
21.50	28 11/16	8,2 11/32	10 3/8	13,4 17/32	20 25/32
21.51	34 15/16	8,2 11/32	8 5/16	10,5 13/32	28,8 19/64
21.52	34 15/16	12,2 31/64	12 7/16	17,6 11/16	23,8 15/16
21.53	45 13/4	12,2 31/64	10 3/8	13,5 17/32	39 117/32
21.54	56 213/64	12,2 31/64	12 7/16	17,6 11/16	47,2 155/64

B BIANCHE - WHITE
delrin® con calotte e sfere inox
delrin® with s/s balls and covers

	D1 mm IN.	D2 mm IN.	D3 mm IN.	S mm IN.	G mm IN.	Carico di lavoro Max working load
21.14	20 25/32	5,3 13/64	8 5/16	12,3 31/64	15,6 5/8	Kg 70
21.15	28 11/16	5,3 13/64	10 3/8	14,6 9/16	20 25/32	Kg 280
21.16	34 15/16	5,3 13/64	12 7/16	18,3 23/32	24 15/16	Kg 280
21.17	34 15/16	5,3 13/64	8 5/16	10,9 27/64	29 19/64	Kg 280
21.18	45 13/4	8,8 11/32	10 3/8	14,6 9/16	37 129/64	Kg 350
21.19	57 21/4	8,8 11/32	12 7/16	18,3 23/32	47 127/32	Kg 350

B NERE - BLACK
delrin® con calotte e sfere inox
delrin® with s/s balls and covers

	D1 mm IN.	D2 mm IN.	D3 mm IN.	S mm IN.	G mm IN.	Carico di lavoro Max working load
21.22	28 11/16	5,3 13/64	8 5/16	11 7/16	21,4 27/32	Kg 280
21.23	28 11/16	5,3 13/64	10 3/8	14,6 9/16	20 25/32	Kg 280
21.24	38 11/2	8,8 11/32	12 7/16	20,6 13/16	28 11/16	Kg 350
21.25	44 147/64	8,8 11/32	14 9/16	21,9 55/64	34 15/16	Kg 350

D delrin® con sfere delrin®
delrin® with delrin® balls

	D1 mm IN.	D2 mm IN.	D3 mm IN.	S mm IN.	G mm IN.	Carico di lavoro Max working load
21.40	29 19/64	5,1 13/64	8 5/16	12,5 1/2	22 7/8	Kg 130
21.41	38 11/2	5,1 13/64	10 3/8	15,9 5/8	29 19/64	Kg 190
21.42	57 21/4	6,1 15/64	12 7/16	19,8 25/32	46,5 153/64	Kg 240



>Pulegge

>Sheaves

