

6 mm [1/4"]

22 mm [7/8"]

Bozzelli a sfere di peso e dimensioni ridotte, usati principalmente su derive per vang, base randa e manovre varie.
Le guance, la puleggia e le sfere sono in delrin®,
le parti metalliche in AISI 316.

These ball bearing blocks are light and compact. Ideal on small boats for control lines, boom vangs and numerous applications.
Delrin® cheeks, sheave and ball bearings.
Stainless steel [AISI 316] load straps.

CARATTERISTICHE BOZZELLO SINGOLO	10.50		SPECIFICATION SINGLE BLOCK
PULEGGIA Ø	mm 22	7/8"	*SHEAVE SIZE*
SCOTTA MAX Ø	mm 6	1/4"	*MAX. LINE SIZE*
ALTEZZA FUORI TUTTO	mm 43	1 3/4"	*OVERALL HEIGHT*
PESO	gr. 17		*WEIGHT*
CARICO DI ROTTURA	Kg. 700		*BREAKING LOAD*
CARICO DI LAVORO	Kg. 100		*MAX WORKING LOAD*

!	Attacco fisso	10.50	*Single*
!	Attacco fisso con arricavo	10.51	*Single with becket*
!	Girevole [carico di rottura Kg 450]	10.52	*Swivel [breaking load Kg 450]*
	Doppio con arricavo	10.54	*Double with becket*
	Doppio	10.55	*Double*
	Triplo	10.56	*Triple*
	Triplo con arricavo	10.57	*Triple with becket*
!	Singolo da incasso [fori Ø mm 5 - interasse fori mm 54]	10.59	*Single thru - deck [holes Ø 3/16" - holes spacing 2 1/8"]*
	Girevole su fascetta [adattabile a pulpiti o candelieri Ø mm 22 - 25]	10.60	*Swivel on curved base [suits 7/8" - 1" tube]*
!	Girevole con grillo [carico di rottura Kg 450]	10.62	*Swivel with shackle [breaking load Kg 450]*
	Triplo con strozzascotte in carbonio su sfere	10.63	*Triple with carbon fibre ball bearing cam cleat*
	Triplo con arricavo e strozzascotte in carbonio su sfere	10.64	*Triple with becket and carbon fibre ball bearing cam cleat*
!	Bozzello piano [fori Ø mm 4 - interasse fori mm 28]	10.65	*Single cheek block [holes Ø 5/32" - holes spacing 1 1/16"]*
	Bozzelli opposti [due 10.50]	10.76	*Linked blocks [two 10.50]*
	Bozzello verticale pivotante [fori Ø mm 4 - interasse fori mm 23]	10.77	*Pivoting lead block [holes Ø 5/32" - holes spacing 29/32"]*
	Bozzello verticale [fori Ø mm 4 - interasse fori mm 23]	10.78	*Upright lead block [holes Ø 5/32" - holes spacing 29/32"]*
	Bozzello verticale doppio [fori Ø mm 4 - interasse fori mm 23]	10.79	*Upright lead double block [holes Ø 5/32" - holes spacing 29/32"]*

! Modelli disponibili **anche senza sfere**.
Per l'ordinazione indicare i codici fra parentesi.

! *Blocks availables **also without balls**.*
For order specify codes into the brackets.

BOZZELLI A SFERE

BALL BEARING BLOCKS



WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT
INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT