8 mm [5/16"]

28 mm [1 1/16"]

Bozzelli a sfere particolarmente scorrevoli e leggeri.
Generalmente impiegati su monotipi e derive per vang, regolazioni di carrelli, barber ecc. ecc.
Le guance, la puleggia e le sfere sono in delrin®, le parti metalliche in AISI 316.

Ball bearing blocks extremely light.
The sheaves run on twin races of Delrin® ball bearings for minimum friction. Usually employed on small boat for traveller regulations, boom vangs and barber haulers.
Delrin® cheeks, sheave and ball bearings.
Stainless steel [AISI 316] load straps.

CARATTERISTICHE BOZZELLO SINGOLO	11.60		SPECIFICATION SINGLE BLOCK
PULEGGIA Ø	mm 28	1 1/16"	*SHEAVE SIZE*
SCOTTA MAX Ø	mm 8	5/16"	*MAX. LINE SIZE*
ALTEZZA FUORI TUTTO	mm 51	2"	*OVERALL HEIGHT*
PESO	gr. 24		*WEIGHT*
CARICO DI ROTTURA	Kg. 750		*BREAKING LOAD*
CARICO DI LAVORO	Kg. 150		*MAX WORKING LOAD*

Attacco fisso	11.60	*Single*	
Attacco fisso con arricavo	11.61	*Single with becket*	
Girevole [carico di rottura Kg 600]	11.62	*Swivel [breaking load Kg 600]*	
! Girevole con grillo [carico di rottura Kg 600]	11.63	*Swivel with shackle [breaking load Kg 600]*	!
! Girevole con grillo e arricavo [carico di rottura Kg 600]	11.64	*Swivel with shackle and becket [breaking load Kg 600]*	!
Doppio	11.65	*Double*	
Doppio con arricavo	11.66	*Double with becket*	
Triplo	11.67	*Triple*	
Triplo con arricavo	11.68	*Triple with becket*	
Singolo da incasso [fori Ø 5 mm - interasse fori 60 mm]	11.69	*Single thru - deck [holes Ø 3/16" - holes spacing 2 3/8"]*	
! Bozzello pivotante con strozzascotte in lega leggera su sfere [fori Ø 5 mm - interasse fori 51 - 16 mm]	11.70	*Swivel block with aluminium ball bearing cam cleat [holes 3/16" - holes axes distance 2" - 5/8"]*	!
Bozzello piano [fori Ø 5 mm - interasse fori 32 mm]	11.71	*Single cheek block [holes Ø 3/16" - holes spacing 1 17/64"]*	
Girevole su fascetta [adattabile a pulpiti o candelieri Ø mm 22 - 25]	11.72	*Swivel on curved base [suits 7/8" - 1" tube]*	
Triplo con strozzascotte in carbonio su sfere	11.73	*Triple with carbon fibre ball bearing cam cleat*	
Triplo con arricavo e strozzascotte in carbonio su sfere	11.74	*Triple with becket and carbon fibre ball bearing cam cleat*	
Due 11.60 montati con anello mm 30 x 5	11.75	*Two 11.60 mounting with ring 1 3/16" x 3/16"*	
Bozzelli opposti [due 11.60]	11.76	*Linked blocks [two 11.60]*	
! Bozzello verticale pivotante [fori Ø mm 5 - interasse fori mm 29]	11.77	*Pivoting lead block [holes Ø 3/16" - holes spacing 1 9/64"]*	!
! Bozzello verticale [fori Ø mm 5 - interasse fori mm 29]	11.78	*Upright lead block [holes Ø 3/16" - holes spacing 1 9/64"]*	!
! Bozzello verticale doppio [fori Ø mm 5 - interasse fori mm 29]	11.79	*Upright lead double block [holes Ø 3/16" - holes spacing 1 9/64"]*	!

! *Bozzelli su sfere inox - inox ball bearing blocks*

! Kit per il montaggio dei bozzelli **11.63 - 11.64** su cavallotto con molla.

! *Kit for assembly of blocks* ***11.63 - 11.64*** *on deck clip with spring.*



BOZZELLI A SFERE

BALL BEARING BLOCKS



WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT WWW.VIADANA.IT

INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT INFO@VIADANA.IT